


# WORK ALL DAY LONG! 3" Chipper/Shredders!



The Discharge Screen is easily removable making the change from screen to screen a breeze.



More screen; 3 additional screens are available on all 3" to 5" chipper/shredders.



Belt Engagement Lever to allow for easy starting.



	Model (Old Mode	Engine* l #)	Size (LxWxH)	Chipper Capacity	Hopper Opening	Chipper Shredders	Weight (Lbs.)	Start	Tires	
	<b>SC3206</b> 70050	Briggs Intek OHV 206cc	40"x22"x46"	3"	12" x 22"	2 chipper blades 8 shredder knives	182	recoil	410/350-4 pneumatic	
	<b>SC3305</b> 70080	Briggs Intek OHV 305cc	40"x22"x46"	3"	12" x 22"	2 chipper blades 12 shredder knives	217	recoil	410/350-4 pneumatic	
	<b>SC3305E</b> 70085	Briggs Intek OHV 305cc	40"x22"x46"	3"	12" x 22"	2 chipper blades 12 shredder knives	232	electric	410/350-4 pneumatic	
	<b>SC3342</b> 75311	Briggs & Stratton	40"x22"x46"	3"	12" x 22"	2 chipper blades 12 shredder knives	232	recoil	410/350-4 pneumatic	

#### options:

70089 - Leaf Tamper

70251 - Blower with 2-Blade radial fan; 360 degree rotation of 4" discharge tube; Adjustable Cap (not available for 70050)



## Find a dealer near you!

Call us at 800.247.7335 or Log onto www.BearCatProducts.com

P.O. Box 849, West Fargo, ND 58078 Email: sales@BearCatProducts.com Fax: 701.282.9522 Models SC3206 (70050), SC3305 (70080), SC3305E (70085), SC3342 (75311)

#### **TWO CHIPPING BLADES**

High chrome content reversible, heat treated chipper steel blades  $[3.125" \times 2" \times .25"]$  quickly chip limbs up to 3" [7.6cm] diameter. The cutting edge is machined at a 45-degree angle for more steel up front. The 45-degree angle also draws the wood into the chipper.

#### SHREDDING EFFICIENCY

Exclusive serrated, free-swinging shredder knives are heat-treated for strength and durability. Two edges, which are easily reversed, double the shredding life. Mounted in a staggered pattern to reduce any dead space.

#### **BALANCED ROTOR**

- 2 chipping blades with 8 to 12 shredder knives depending on model.
- Belt Drive
- Rotor weighs 16.4 lbs., 3800 rpm

#### **BUILT TO LAST**

- Extra strength and reinforcements in areas that matter most
- Built to last with 16 gauge steel construction.

#### **LARGE HOPPER**

• Extra wide, extra deep, 15.75" x 7.5"

# ALL 3" [7.6CM] MODELS HAVE STANDARD COURSE SCREEN - 1.5" HOLES

#### **DISCHARGE SCREEN**

- Heavy-duty discharge screens available in 4 different sizes to fit your particular needs.
- Quick and easy to change

#### **STABILITY**

Wide tire track and full width front leg give maximum stability.

#### **TOWING**

There are two different types of tow hitches available.

- The 70098 is a Standard Tow Hitch
- The 71113 is a Fold Up Tow Hitch makes moving from job site to job site in a hurry.

#### **DIAMOND SHAPED CHIPPER CHUTE**

Enables you to insert most irregular limbs even if they have some knobs on them.

#### **PNEUMATIC TIRES WITH GREASE ZERKS**

• Wheels feature grease zerks, enabling easy greasing of the hub.

#### **DIMENSIONS:**

- SC3206 (70050) Length: 40", Width: 22", Height: 46"
- SC3305 (70080) Length: 40", Width: 22", Height: 46"
- SC3305E (70085) Length: 40", Width: 22", Height: 46"
- SC3342 (75311) Length: 40", Width: 22", Height: 46"

#### **DECIBEL LEVELS:**

- SC3206 (70050) 111 decibels
- SC3305 (70080) 112 decibels
- SC3305E (70085) 112 decibels
- SC3342 (75311) 114 decibels

Noise Emission Directive 2000/14/EC

#### **SAFETY**

Meets all applicable ANSI safety standards.

#### **OPTIONS FOR MODEL 70050:**

- 70089 Leaf Tamper
- 70312 Fine Screen: .375" Holes
- 70314 Medium Screen: .75" Holes
- 70492 Wet Debris Screen
- 70310 Standard Coarse Screen

#### **OPTIONS FOR MODELS 70080, 70085, 75311:**

- 70089 Leaf Tamper
- 70251 Blower Attachment Package (ALL MODELS EXCEPT 70050)
- 70303 Fine Screen: .375" Holes
- 70305 Medium Screen: .75" Holes
- 70494 Wet Debris Screen
- 70301 Standard Coarse Screen



## Find a dealer near you!

Call us at 800.247.7335 or Log onto www.BearCatProducts.com

> P.O. Box 849, West Fargo, ND 58078 Email: sales@BearCatProducts.com Fax: 701.282.9522